



# PRO SERIES

# EMBOSSER 1000



## FEATURES

standard



optional



## USED BY

Banks/Credit Institutions  
 Insurance Companies  
 Casino  
 Clubs/Associations  
 Government Offices  
 Department Stores  
 Service Bureaus

## IDEAL FOR

Credit cards and other  
 Financial cards\*  
 Gift cards  
 ID cards  
 Prepaid cards  
 \* compatible with most 3rd party  
 EMV personalization software  
 solutions

## IN LINE SOLUTIONS

MULTIFEEDER 6000  
 THERMAL 1000/2000  
 INSERTER 3000  
 LABEL DISPENSER 1500

## SOFTWARE



## INCLUDED



## CARD EMBOSSING

## DESKTOP DIMENSION WITH HEAVY DUTY PERFORMANCE



105-character capacity drum  
 One pass front and rear infill (optional)  
 Encoding:  
 - Magnetic encoding and chip contact station (JIS/ISO)  
 - Regular VISA + VISA mini card personalization (paired)







# PRO SERIES

# EMBOSSER 1000

## SPECIFICATIONS



<b>input hopper</b>	200 cards
<b>output hopper</b>	200 cards
<b>reject hopper</b>	10 cards capacity
<b>card format</b>	CR80 - ISO standard
<b>card thickness</b>	ISO 7810 0,76 mm ± 0,08 / 30 mil ± 3
<b>card materials</b>	ABS, PVC and composite; semi transparent (available on request)
<b>internal tipper unit</b>	Off-line tipping option (76 x 41 mm area / 3 x 1.61 in). Ribbon saving function
<b>embossing area</b>	9 lines x 31 characters (76 x 45 mm area / 3 x 1.77 in)
<b>drum capacity</b>	105 characters
<b>embossing characters</b>	Standard Gothic, OCR7B, country specific characters (optional), Braille drum/types (optional)
<b>dual infill</b>	Optional: front infill (available fonts OCRB1/B4 and others) or rear infill device (CVV2-OCRA1) for front/rear infilling in one pass. Possibility to have only front/only rear pass
<b>performance</b>	Approx. 500 CPH
<b>magnetic encoding</b>	Optional: 3 ISO 7811 tracks, LoCo, HiCo, JIS Optional: regular VISA + VISA mini card (paired)
<b>chip contact station</b>	Optional
<b>contactless station</b>	Available on request
<b>communication interface</b>	RS232 serial port
<b>power supply</b>	100 - 117 - 220 - 230 or 240 Volts - 50 or 60 Hz
<b>operating environment</b>	5°C - 40°C / 41°F to 104°F
<b>dimensions (WxDxH)</b>	860 x 480 x 350 mm / 33.9" x 18.9" c 13.8" in
<b>weight</b>	62 Kg / 137 lbs
<b>floor stand</b>	Optional (required for in-line operation)
<b>operating systems</b>	Multicard 2006 operating with Windows 2000/XP
<b>application program</b>	User interface monitoring, card production control, automatic card remake option, pre-encoded card reading with complete processing operation, system status and help messages displayed on Personal Computer
<b>in-line configuration</b>	The Pro Series units can operate in a stand alone or in-line configuration with 2 up to 5 equipments. The EMBOSSER 1000 can be connected to: MULTIFEEDER 6000, THERMAL 1000/2000, INSERTER 3000, LABEL DISPENSER 1500

**CONVENIENT:** the EMBOSSER 1000 is part of a tried and tested CIM product range. It combines desktop dimension with heavy duty performance. FIFO (first in - first out) input hopper with a 200 card capacity

**FAST:** with its integrated MSP (Multi Smart Processing) system the EMBOSSER 1000 can process up to 3 cards simultaneously

**VERSATILE:** embossing, infill and tipping with magnetic stripe and/or smart card management into one single operation, the EMBOSSER 1000 can be fitted with special embossing characters to personalize international credit cards, such as VISA and MasterCard (all country specific characters), and perform dual infill personalization of the front and back in one pass

Data subject to change without notice. All stated trademarks belong to their respective owners. Rev. 01 - 10/06



**MF Group SpA - CIM division**  
 OFFICE/ FACTORY: Via O. Serra, 2 - 40012 Calderara di Reno (BO) - Italy  
 T. +39 051 6465 011 - Fax +39 051 6465 012 - www.cimitaly.it - info@cimitaly.it  
 HEADQUARTERS: Loc. Braine, 54/a - 40036 Rioveggio (BO) - Italy

